18V POE ADAPTER





DC OUTPUT (O/P)	DC voltage (three way)	18 V
	Rated current	0.7 A
	Current range	0 - 0.7 A
	Ripple and noise (max)	180 mVp-p
	Rated power	12.6 W
	Voltage tolerance	+/- 4%
	Rising time	500 ms, 50 ms at full load
	Hold up time	>5 ms at full load
Input (I/P)	Rated voltage range	100 - 240 VAC
	Frequency range	47 - 63 Hz
	Efficiency	>80% (min)
	AC current	0.27 A (max)
	Leakage current	< 0.25 mA at 250 V
	Inrush current	< 40 A at 230 V
	Surge test standard	IEC 6100-4-5
	Max surge discharge	1200 A (8/20 uS) power
	Peak pulse current	36 A (10/1000 uS) data
Protection	Short circuit time	Hiccup mode, no damage for permanent short circuit
	Overload type	115 - 200% rated output power and hiccup mode, automatic recovering
	Over power type	115 - 200% rated output power and hiccup mode, automatic recovering
Safety and EMC	Standard	EN60950
	Withstand voltage	I/P - O/P: 1.5 KVAC, 5 mA, 60 s
	Isolation resistance	I/P - O/P: 100 M ohms/ 500 VDC
	EMC	EN55022 Class B
Other	Certification	CE, FCC, UL
	MTBF	300 Khrs, Mil-HDBK-217F (25 C)
	Connectors	3 pin AC plug, 2 x shielded RJ-45 connectors
	Dimensions	4.5 x 3 x 9.5 cm or 1.77 x 1.18 x 3.74 inch
	Weight	105 g
	RoHS compliance	Yes

Copyright © 2012 Deliberant LLC. All rights reserved. Deliberant, the Deliberant logo, are trademarks of Deliberant LLC. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, Deliberant does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice.





www.deliberant.com

Copyright © 2012 Deliberant LLC. All rights reserved. Deliberant, the Deliberant logo, are trademarks of Deliberant LLC. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, Deliberant does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice.

